



DC AXIAL FANS

DS SERIES 60×60×20 mm

- * Material: Impeller & Frame: Plastic (UL 94V-0)
- * Lead Wires: UL 1007 AWG #26 or Equivalent
- * Impeller: 7 Blades
- * Rotational direction CCW view from front face
- * Weight: 50g (1.43 OZ)

MODEL		Bearing Type	Rated Voltage	Operating Voltage Range	Rated Current	Rated Input Power	Speed	Maximum Air Flow		Maximum Air Pressure		Acoustic Noise	Life expectancy L ₁₀ @40°C
PART NO.	SIGNAL	B.T.S.R	VDC	VDC	Amp	Watt	R.P.M.	m ³ /min	CFM	mmH ₂ O	IN H ₂ O	dB-A	hours
DS06020_12E	-FG	B I B	12	5.0 to 13.2	0.08	0.96	2200	0.306	10.82	1.43	0.056	20.2	70000
DS06020_12L	-FG	B I B	12	5.0 to 13.2	0.10	1.20	3000	0.424	14.96	2.47	0.097	24.9	70000
DS06020_12M	-FG	B I B	12	5.0 to 13.2	0.15	1.80	4000	0.626	22.10	4.22	0.166	31.7	70000
* DS06020_12H	-FG	B I B	12	5.0 to 13.2	0.23	2.76	5000	0.759	26.80	6.36	0.251	39.9	70000
DS06020_12U	-FG	B	12	5.0 to 13.2	0.35	4.20	5800	0.917	32.37	8.47	0.333	42.8	70000
DS06020_12S	-FG	B	12	5.0 to 13.2	0.45	5.40	6800	1.113	39.32	10.67	0.420	47.4	70000

