

# DC AXIAL FANS



## DA SERIES 120×120×32 mm 48v

- \* Material: Impeller & Frame: Plastic (UL 94V-0)
- \* Lead Wires: UL 1007 AWG #24 or Equivalent
- \* Impeller: 5 Blades
- \* Rotational direction CCW view from front face
- \* Weight: 273g (9.63 OZ)

MODEL		Bearing Type	Rated Voltage	Operating Voltage Range		Rated Current	Rated Input Power	Speed	Maximum Air Flow		Maximum Air Pressure		Acoustic Noise	Life expectancy L <sub>10@40°C</sub>
PART NO.	SIGNAL	B.T.S.R	VDC	VDC	Amp	Watt	R.P.M.	m <sup>3</sup> /min	CFM	mmH <sub>2</sub> O	IN H <sub>2</sub> O	dB-A	hours	
DA12032_48E	-FG/RD	B	48	36.0 to 56.0	0.05	2.40	1900	1.596	56.38	3.52	0.138	32.0	160000	
DA12032_48L	-FG/RD	B	48	36.0 to 56.0	0.07	3.36	2500	2.145	75.75	6.32	0.248	40.5	140000	
DA12032_48M	-FG/RD	B	48	36.0 to 56.0	0.09	4.32	3150	2.714	95.85	9.98	0.393	47.0	120000	
* DA12032_48H	-FG/RD	B	48	36.0 to 56.0	0.14	6.72	3800	3.299	116.53	14.18	0.558	51.0	100000	
* DA12032_48U	-FG/RD	B	48	36.0 to 56.0	0.23	11.04	4400	3.782	133.56	18.32	0.721	55.5	90000	

