

DC AXIAL FANS

DA SERIES Ø172×51 mm 12v,48v



- * Material: Impeller: Plastic (UL 94V-0) & Frame: Diecast Alminum
- * Lead Wires: UL 1007 AWG #24 or Equivalent
- * Impeller: 5 Blades
- * Rotational direction CCW view from front face
- * Weight: 980g (34.57 OZ)

ASIA VITAL COMPONENTS CO., LTD. Six Sigma

MODEL	Bearing Type	Rated Voltage	Operating Voltage Range	Rated Current	Rated Input Power	Speed	Maximum Air Flow	Maximum Air Pressure	Acoustic Noise	Life expectancy L ₁₀ @40°C			
PART NO.	SIGNAL	B.T.S.R	VDC	VDC	Amp	Watt	R.P.M.	m ³ /min	CFM	mmH ₂ O	IN H ₂ O	dB-A	hours
DA17251_12L	-FG/RD	B	12	7 to 13.2	2.1	25.2	3700	7.30	257.67	26.10	1.03	60	180000
DA17251_12M	-FG/RD	B	12	7 to 13.2	3.4	40.8	4300	8.62	304.57	35.50	1.40	63	180000
* DA17251_12H	-FG/RD	B	12	7 to 13.2	5.1	61.2	4900	9.93	350.63	44.30	1.74	66	130000
DA17251_48L	-FG/RD	B	48	32 to 56	0.5	24	3700	7.30	257.67	26.10	1.03	60	180000
DA17251_48M	-FG/RD	B	48	32 to 56	0.88	42.2	4300	8.62	304.57	35.50	1.40	63	180000
DA17251_48H	-FG/RD	B	48	32 to 56	1.1	52.8	4900	9.93	350.63	44.30	1.74	66	130000
* DA17251_48U	-FG/RD	B	48	32 to 56	1.6	76.8	5500	11.11	392.52	53.30	2.10	68	130000

