

# DC AXIAL FANS

## DAKA SERIES 92×92×25 mm

- \* Material: Impeller & Frame: Plastic (UL 94V-0)
- \* Lead Wires: UL 1007 AWG #24 or Equivalent
- \* Impeller: 9 Blades
- \* Rotational direction CCW view from front face
- \* Weight: 132g (4.65 OZ)



ASIA VITAL COMPONENTS CO., LTD. Six Sigma

MODEL	Bearing Type	Rated Voltage	Operating Voltage Range		Rated Current	Rated Input Power	Speed	Maximum Air Flow		Maximum Air Pressure		Acoustic Noise	Life expectancy L <sub>10</sub> @40°C
PART NO.	SIGNAL	B.T.S.R	VDC	VDC	Amp	Watt	R.P.M.	m <sup>3</sup> /min	CFM	mmH <sub>2</sub> O	IN H <sub>2</sub> O	dB-A	hours
DAKA0925_2E	FG	B	12	5 to 13.2	0.3	3.6	2000	1.204	42.51	2.53	0.100	30.02	70000
DAKA0925_2L	FG	B	12	5 to 13.2	0.5	6	2600	1.617	57.07	4.46	0.176	37.77	70000
DAKA0925_2M	FG	B	12	5 to 13.2	0.8	9.6	3200	2.071	73.10	6.86	0.270	43.33	70000
DAKA0925_2H	FG	B	12	5 to 13.2	1.2	14.4	3800	2.484	87.66	9.93	0.391	48.66	70000
DAKA0925_2U	FG	B	12	5 to 13.2	2.0	24	4600	3.019	106.55	14.10	0.551	54.12	70000

