

DC AXIAL FANS

DATA SERIES 120×120×32 mm 12v,48v

- * Material: Impeller & Frame: Plastic (UL 94V-0)
- * Lead Wires: UL 1007 AWG #24 or Equivalent
- * Impeller: 7 Blades
- * Rotational direction CCW view from front face
- * Weight: 240g (8.47 OZ)



ASIA VITAL COMPONENTS CO., LTD. Six Sigma

MODEL	Bearing Type	Rated Voltage	Operating Voltage Range		Rated Current	Rated Input Power	Speed	Maximum Air Flow		Maximum Air Pressure		Acoustic Noise	Life expectancy L _{10@40°C}
PART NO.	SIGNAL	B.T.S.R	VDC	VDC	Amp	Watt	R.P.M.	m ³ /min	CFM	mmH ₂ O	IN H ₂ O	dB-A	hours
DATA1232_2E	-FG/RD	B	12	7.0 to 13.2	0.15	1.80	1900	2.05	72.3	3.1	0.12	33.1	140000
DATA1232_2L	-FG/RD	B	12	7.0 to 13.2	0.27	3.24	2500	2.70	95.2	5.3	0.21	41.4	120000
DATA1232_2M	-FG/RD	B	12	7.0 to 13.2	0.44	5.28	3150	3.40	119.9	8.4	0.33	48.1	100000
* DATA1232_2H	-FG/RD	B	12	7.0 to 13.2	0.72	8.64	3800	4.10	144.7	12.3	0.48	53.3	100000
* DATA1232_2U	-FG/RD	B	12	7.0 to 13.2	1.11	13.32	4300	4.64	163.7	15.7	0.62	56.8	100000
DATA1232_8E	-FG/RD	B	48	28.0 to 56.0	0.06	2.88	1900	2.05	72.3	3.1	0.12	33.1	140000
DATA1232_8L	-FG/RD	B	48	28.0 to 56.0	0.08	3.84	2500	2.70	95.2	5.3	0.21	41.4	120000
* DATA1232_8M	-FG/RD	B	48	28.0 to 56.0	0.13	6.24	3150	3.40	119.9	8.4	0.33	48.1	100000
DATA1232_8H	-FG/RD	B	48	28.0 to 56.0	0.19	9.12	3800	4.10	144.7	12.3	0.48	53.3	100000
* DATA1232_8U	-FG/RD	B	48	28.0 to 56.0	0.28	13.44	4300	4.64	163.7	15.7	0.62	56.8	100000

