

# DC AXIAL FANS

## DB SERIES 40×40×28 mm

- \* Material: Impeller & Frame: Plastic (UL 94V-0)
- \* Lead Wires: UL 1007 AWG #26 or Equivalent
- \* Impeller: 5 Blades
- \* Rotational direction CCW view from front face
- \* Weight: 40g (1.41 OZ)



MODEL		Bearing Type	Rated Voltage	Operating Voltage Range	Rated Current	Rated Input Power	Speed	Maximum Air Flow	Maximum Air Pressure	Acoustic Noise	Life expectancy L <sub>10@40°C</sub>		
PART NO.	SIGNAL	B.T.S.R	VDC	VDC	Amp	Watt	R.P.M.	m <sup>3</sup> /min	CFM	mmH <sub>2</sub> O	IN H <sub>2</sub> O	dB-A	hours
DB04028_12L	-FG / RD	B	12	7.0 to 13.2	0.14	1.68	8000	0.401	13.86	11.60	0.456	40.0	120000
DB04028_12M	-FG / RD	B	12	7.0 to 13.2	0.23	2.76	9500	0.449	15.85	17.57	0.692	45.0	120000
DB04028_12H	-FG / RD	B	12	7.0 to 13.2	0.38	4.56	11000	0.542	18.73	23.38	0.920	50.5	110000
DB04028_12U	-FG / RD	B	12	7.0 to 13.2	0.55	6.60	13000	0.673	23.78	33.65	1.324	54.0	100000
* DB04028_12S	-FG / RD	B	12	7.0 to 13.2	0.64	7.68	15000	0.703	24.82	41.61	1.638	58.0	100000

