

# DC AXIAL FANS

## DBTA SERIES 40x40x20 mm

- \* Material: Impeller & Frame: Plastic (UL 94V-0)
- \* Lead Wires: UL 1061 AWG #28 or Equivalent
- \* Impeller: 7 Blades
- \* Rotational direction CCW view from front face
- \* Weight: 25g (0.88 OZ)



ASIA VITAL COMPONENTS CO., LTD. Six Sigma

MODEL		Bearing Type	Rated Voltage	Operating Voltage Range		Rated Current	Rated Input Power	Speed	Maximum Air Flow		Maximum Air Pressure		Acoustic Noise	Life expectancy L <sub>10</sub> @40°C
PART NO.	SIGNAL	B.T.S.R	VDC	VDC	Amp	Watt	R.P.M.	m <sup>3</sup> /min	CFM	mmH <sub>2</sub> O	IN H <sub>2</sub> O	dB-A	hours	
DBTA0420B_2E	-FG / RD	B	12	7.0 to 13.2	0.08	0.96	8000	0.267	9.43	8.92	0.351	32.9	70000	
DBTA0420B_2L	-FG / RD	B	12	7.0 to 13.2	0.11	1.32	10000	0.332	11.73	13.96	0.549	40.0	70000	
DBTA0420B_2M	-FG / RD	B	12	7.0 to 13.2	0.17	2.04	12000	0.405	14.31	20.06	0.789	44.3	70000	
DBTA0420B_2H	-FG / RD	B	12	7.0 to 13.2	0.25	3.00	14000	0.476	16.82	27.34	1.073	48.9	70000	
* DBTA0420B_2U	-FG / RD	B	12	7.0 to 13.2	0.41	4.92	16000	0.561	19.82	36.55	1.438	52.9	70000	

