

DC AXIAL FANS



DBTA SERIES 40×40×28 mm

- * Material: Impeller & Frame: Plastic (UL 94V-0)
- * Lead Wires: UL 1061 AWG #26 or Equivalent
- * Impeller: 5 Blades
- * Rotational direction CCW view from front face
- * Weight: 45g (1.58 OZ)

ASIA VITAL COMPONENTS CO., LTD. Six Sigma

MODEL	Bearing Type	Rated Voltage	Operating Voltage Range	Rated Current	Rated Input Power	Speed	Maximum Air Flow	Maximum Air Pressure	Acoustic Noise	Life expectancy L ₁₀ @40°C			
PART NO.	SIGNAL	B.T.S.R	VDC	VDC	Amp	Watt	R.P.M.	m ³ /min	CFM	mmH ₂ O	IN H ₂ O	dB-A	hours
DBTA0428_2L	-FG/RD	B	12	7.0 to 13.8	0.11	1.32	8500	0.349	12.34	10.60	0.417	38.7	120000
DBTA0428_2M	-FG/RD	B	12	7.0 to 13.8	0.13	1.56	10000	0.406	14.34	14.18	0.558	42.4	110000
DBTA0428_2H	-FG/RD	B	12	7.0 to 13.8	0.35	4.20	14500	0.586	20.68	26.33	1.037	52.9	90000
DBTA0428_2U	-FG/RD	B	12	7.0 to 13.2	0.45	5.40	16000	0.663	23.42	35.80	1.409	55.4	70000
* DBTA0428_2S	-FG/RD	B	12	7.0 to 13.2	0.62	7.44	18000	0.754	26.64	44.52	1.753	58.0	70000

