

DC AXIAL FANS

DBTA SERIES 120×120×25 mm

- * Material: Impeller & Frame: Plastic (UL 94V-0)
- * Lead Wires: UL 1007 AWG #24 or Equivalent
- * Impeller: 9 Blades
- * Rotational direction CCW view from front face
- * Weight: 250g (8.82 OZ)



ASIA VITAL COMPONENTS CO., LTD. Six Sigma

MODEL	Bearing Type	Rated Voltage	Operating Voltage Range	Rated Current	Rated Input Power	Speed	Maximum Air Flow	Maximum Air Pressure	Acoustic Noise	Life expectancy L ₁₀ @40°C			
PART NO.	SIGNAL	B.T.S.R	VDC	VDC	Amp	Watt	R.P.M.	m ³ /min	CFM	mmH ₂ O	IN H ₂ O	dB-A	hours
DBTA1225_2L	-FG/RD	B	12	7.0 to 13.2	0.54	6.48	3100	3.069	108.38	8.05	0.317	49.0	120000
* DBTA1225_2M	-FG/RD	B	12	7.0 to 13.2	0.62	7.44	3400	3.340	117.96	9.50	0.374	51.5	120000
* DBTA1225_2H	-FG/RD	B	12	7.0 to 13.2	0.71	8.52	3700	3.682	130.04	11.38	0.448	54.0	120000
* DBTA1225_2U	-FG/RD	B	12	7.0 to 13.2	0.84	10.08	4000	3.985	140.75	13.51	0.532	55.5	120000
* DBTA1225_2S	-FG/RD	B	12	7.0 to 13.2	1.19	14.28	4500	4.549	160.66	17.37	0.684	58.5	110000

