

# DC AXIAL FANS

## DCTA SERIES 92x92x38 mm 12v,48v

- \* Material: Impeller & Frame: Plastic (UL 94V-0)
- \* Lead Wires: UL 1007 AWG #24 or Equivalent
- \* Impeller: 9 Blades
- \* Rotational direction CCW view from front face
- \* Weight: 270g (9.52 OZ)



ASIA VITAL COMPONENTS CO., LTD. Six Sigma

MODEL	Bearing Type	Rated Voltage	Operating Voltage Range	Rated Current	Rated Input Power	Speed	Maximum Air Flow	Maximum Air Pressure	Acoustic Noise	Life expectancy L <sub>10</sub> @40°C			
PART NO.	SIGNAL	B.T.S.R	VDC	VDC	Amp	Watt	R.P.M.	m <sup>3</sup> /min	CFM	mmH <sub>2</sub> O	IN H <sub>2</sub> O	dB-A	hours
DCTA0938_2M	-FG/RD	B	12	7 to 13.2	0.68	8.16	5700	2.544	89.83	18.66	0.735	53.1	140000
DCTA0938_2H	-FG/RD	B	12	7 to 13.2	1.08	13.0	7000	3.163	111.71	28.47	1.121	58.7	130000
* DCTA0938_2U	-FG/RD	B	12	7 to 13.2	1.60	19.2	8300	3.671	129.64	39.28	1.546	62.8	130000
DCTA0938_8M	-FG/RD	B	48	36.0 to 56.0	0.18	8.64	5700	2.544	89.83	18.66	0.735	53.1	140000
DCTA0938_8H	-FG/RD	B	48	36.0 to 56.0	0.25	12.0	7000	3.163	111.71	28.47	1.121	58.7	130000
* DCTA0938_8U	-FG/RD	B	48	36.0 to 56.0	0.37	17.76	8300	3.671	129.64	39.28	1.546	62.8	130000

