

DC AXIAL FANS

2B SERIES 92×92×38 mm

- * Material: Impeller & Frame: Plastic (UL 94V-0)
- * Lead Wires: UL 1007 AWG #24 or Equivalent
- * Impeller: 9 Blades
- * Rotational direction CCW view from front face
- * Weight: 270g (9.52 OZ)



ASIA VITAL COMPONENTS CO., LTD. Six Sigma

MODEL		Bearing Type	Rated Voltage	Operating Voltage Range	Rated Current	Rated Input Power	Speed	Maximum Air Flow	Maximum Air Pressure	Acoustic Noise	Life expectancy L ₁₀ @40°C		
PART NO.	SIGNAL	B.T.S.R	VDC	VDC	Amp	Watt	R.P.M.	m ³ /min	CFM	mmH ₂ O	IN H ₂ O	dB-A	hours
2B09238_12E	-FG/RD	B	12	7.0 to 13.2	0.22	2.64	3000	1.707	60.28	7.26	0.286	40.0	140000
2B09238_12L	-FG/RD	B	12	7.0 to 13.2	0.41	4.92	4000	2.295	81.05	12.6	0.496	47.2	140000
2B09238_12M	-FG/RD	B	12	7.0 to 13.2	0.7	8.4	5000	2.869	101.32	18.6	0.732	54.1	130000
2B09238_12H	-FG/RD	B	12	7.0 to 13.2	1.25	15.0	6000	3.496	123.46	27.8	1.095	58.6	130000
2B09238_12U	-FG/RD	B	12	7.0 to 13.2	2.0	24.0	7000	4.150	146.57	37.9	1.492	62.4	130000
* 2B09238_12S	-FG/RD	B	12	7.0 to 13.2	3.1	37.2	8000	4.654	164.34	46.8	1.843	65.8	120000

