

DC AXIAL FANS

2B SERIES 120x120x38 mm 12v, 48v

- * Material: Impeller & Frame: Plastic (UL 94V-0)
- * Lead Wires: UL 1007 AWG #24 or Equivalent
- * Impeller: 11 Blades
- * Rotational direction CCW view from front face
- * Weight: 450g (15.87 OZ)



ASIA VITAL COMPONENTS CO., LTD. Six Sigma

MODEL	Bearing Type	Rated Voltage	Operating Voltage Range	Rated Current	Rated Input Power	Speed	Maximum Air Flow	Maximum Air Pressure	Acoustic Noise	Life expectancy L ₁₀ @40°C			
PART NO.	SIGNAL	B.T.S.R	VDC	VDC	Amp	Watt	R.P.M.	m ³ /min	CFM	mmH ₂ O	IN H ₂ O	dB-A	hours
2B12038_12M	-FG/RD	B	12	7.0 to 13.2	1.52	18.24	4000	4.857	171.46	17.8	0.701	59.5	132500
2B12038_12H	-FG/RD	B	12	7.0 to 13.2	2.40	28.80	4800	5.844	206.28	26.2	1.031	65.0	125000
* 2B12038_12U	-FG/RD	B	12	7.0 to 13.2	3.88	46.56	5500	6.649	234.71	34.4	1.354	68.5	115000
* 2B12038_48M	-FG/RD	B	48	28.0 to 56.0	0.36	17.28	4000	4.857	171.46	17.8	0.701	59.5	132500
* 2B12038_48H	-FG/RD	B	48	28.0 to 56.0	0.58	27.84	4800	5.844	206.28	26.2	1.031	65.0	125000
* 2B12038_48U	-FG/RD	B	48	28.0 to 56.0	0.93	44.64	5500	6.649	234.71	34.4	1.354	68.5	115000
* 2B12038_48S	-FG/RD	B	48	28.0 to 56.0	1.27	60.96	6200	7.530	265.82	44.2	1.740	71.5	115000

