



DC AXIAL FANS

DASA SERIES 25×25×10 mm 5v

- * Material: Impeller & Frame: Plastic (UL 94V-0)
- * Lead Wires: UL 1061 AWG #28 or Equivalent
- * Impeller: 5 Blades
- * Rotational direction CCW view from front face
- * Weight: 35g (1.23 OZ)

MODEL		Bearing Type	Rated Voltage	Operating Voltage Range	Rated Current	Rated Input Power	Speed	Maximum Air Flow		Maximum Air Pressure		Acoustic Noise	Life expectancy L10@40°C
PART NO.	SIGNAL	B.T.S.R	VDC	VDC	Amp	Watt	R.P.M.	m ³ /min	CFM	mmH ₂ O	IN H ₂ O	dB-A	hours
* DASA2510_5U	-FG/RD	B R	5	3 to 5.5	0.25	1.25	13000	0.179	3.16	4.7	0.185	27.9	50000
DASA2510_5H	-FG/RD	B R	5	3 to 5.5	0.13	0.65	11000	0.151	2.67	3.72	0.147	24.4	50000
DASA2510_5M	-FG/RD	B R	5	3 to 5.5	0.10	0.5	9000	0.062	2.16	2.27	0.090	19.8	50000
DASA2510_5L	-FG/RD	B R	5	3 to 5.5	0.04	0.2	7000	0.042	1.5	1.58	0.062	17.3	50000

