

DC AXIAL FANS

DA SERIES
50x50x15 mm 12v, 5v

- * Material: Impeller & Frame: Plastic (UL 94V-0)
- * Lead Wires: UL 1007 AWG #26 or Equivalent
- * Impeller: 7 Blades
- * Rotational direction CCW view from front face
- * Weight: 31g (1.09 OZ)



MODEL	Bearing Type	Rated Voltage	Operating Voltage Range	Rated Current	Rated Input Power	Speed	Maximum Air Flow	Maximum Air Pressure	Acoustic Noise	Life expectancy L ₁₀ @40°C			
PART NO.	SIGNAL	B.T.S.R	VDC	VDC	Amp	Watt	R.P.M.	m ³ /min	CFM	mmH ₂ O	IN H ₂ O	dB-A	hours
DA05015_12E	-FG	B B	12	5.0 to 13.2	0.09	1.08	3600	0.278	9.80	2.12	0.084	23.4	70000
DA05015_12L	-FG	B B	12	5.0 to 13.2	0.12	1.44	4200	0.340	11.90	2.94	0.116	26.7	70000
DA05015_12M	-FG	B B	12	5.0 to 13.2	0.15	1.80	4700	0.379	13.40	3.48	0.137	28.3	70000
* DA05015_12H	-FG	B	12	5.0 to 13.2	0.20	2.40	5400	0.425	15.01	4.54	0.179	31.5	70000
DA05015_12U	-FG	B	12	5.0 to 13.2	0.40	4.80	6000	0.495	17.49	5.85	0.230	35.5	70000
DA05015_05E	-FG	B	5	4.0 to 5.5	0.15	0.75	3600	0.278	9.80	2.12	0.084	23.4	70000
DA05015_05L	-FG	B	5	4.0 to 5.5	0.20	1.00	4200	0.340	11.99	2.94	0.116	26.7	70000
DA05015_05M	-FG	B	5	4.0 to 5.5	0.25	1.25	4700	0.379	13.40	3.48	0.137	28.3	70000
DA05015_05H	-FG	B	5	4.0 to 5.5	0.30	1.50	5400	0.425	15.01	4.54	0.179	31.5	70000
DA05015_05U	-FG	B	5	4.0 to 5.5	0.40	2.00	6000	0.495	17.49	5.85	0.230	35.5	70000

