

# DC AXIAL FANS



## DESA SERIES 92×92×38 mm

- \* Material: Impeller & Frame: Plastic (UL 94V-0)
- \* Lead Wires: UL 1007 AWG #24 or Equivalent
- \* Impeller: 5 Blades
- \* Rotational direction CCW view from front face
- \* Weight: 150g (4.221 OZ)

ASIA VITAL COMPONENTS CO., LTD. Six Sigma

MODEL	PART NO.	SIGNAL	Bearing Type		Rated Voltage	Operating Voltage Range	Rated Current	Rated Input Power	Speed	Maximum Air Flow		Maximum Air Pressure		Acoustic Noise	Life expectancy L <sub>10</sub> @40°C	
			B	I						T	S	R	m <sup>3</sup> /min			CFM
	DESA0938_12X	-FG/RD	B	I	R	12	5.0 to 13.2	0.30	3.60	2500	1.286	45.38	4.71	0.185	30.9	70000
	DESA0938_12E	-FG/RD	B	I	R	12	5.0 to 13.2	0.38	4.56	3000	1.550	54.73	6.43	0.253	36.0	70000
	DESA0938_12L	-FG/RD	B	I	R	12	5.0 to 13.2	0.53	6.36	3500	1.836	64.80	8.65	0.341	40.8	70000
*	DESA0938_12M	-FG/RD	B	I	R	12	5.0 to 13.2	0.75	9.00	4000	2.141	75.56	11.75	0.463	44.8	70000
	DESA0938_12H	-FG/RD	B	I	R	12	5.0 to 13.2	0.90	10.80	5000	2.626	92.69	15.53	0.611	51.2	70000

