

DC AXIAL FANS



DS SERIES 80×80×15 mm 12v,24v

- * Material: Impeller & Frame: Plastic (UL 94V-0)
- * Lead Wires: UL 1007 AWG #26 or Equivalent
- * Impeller: 9 Blades
- * Rotational direction CCW view from front face
- * Weight: 55g (1.45 OZ)

MODEL		Bearing Type	Rated Voltage	Operating Voltage Range	Rated Current	Rated Input Power	Speed	Maximum Air Flow		Maximum Air Pressure		Acoustic Noise	Life expectancy L ₁₀ @40°C	
PART NO.	SIGNAL	B.T.S.R	VDC	VDC	Amp	Watt	R.P.M.	m ³ /min	CFM	mmH ₂ O	IN H ₂ O	dB-A	hours	
*	DS08015_12L	-FG/RD	<u>B I</u>	12	5.0 to 13.2	0.42	5.04	2500	0.676	23.86	2.57	0.101	27.2	70000
	DS08015_12M	-FG/RD	<u>B I</u>	12	5.0 to 13.2	0.48	5.76	3400	0.950	33.54	4.56	0.180	35.1	70000
	DS08015_12H	-FG/RD	<u>B I</u>	12	5.0 to 13.2	0.50	6.00	4000	1.083	38.26	6.24	0.246	39.8	70000
	DS08015_12U	-FG/RD	<u>B I</u>	12	5.0 to 13.2	0.60	7.20	5000	1.398	49.35	9.27	0.365	45.5	70000
	DS08015_24M	-FG/RD	B	24	10.0 to 26.4	0.38	9.12	3100	0.840	29.68	3.32	0.131	31.4	70000

