

DC AXIAL FANS

DV SERIES 70×70×20 mm

* Material: Impeller & Frame: Plastic (UL 94V-0)

* Lead Wires: UL 1061 AWG #26 or Equivalent

* Impeller: 7 Blades

* Rotational direction CCW view from front face

* Weight: 65g (2.29 OZ)



MODEL		Bearing Type	Rated Voltage	Operating Voltage Range	Rated Current	Rated Input Power	Speed	Maximum Air Flow		Maximum Air Pressure		Acoustic Noise	Life expectancy L ₁₀ @40°C
PART NO.	SIGNAL	B.T.S.R	VDC	VDC	Amp	Watt	R.P.M.	m ³ /min	CFM	mmH ₂ O	IN H ₂ O	dB-A	hours
DV07020_12E	-FG/RD	B	12	5.0 to 13.2	0.20	2.40	3600	0.673	23.76	4.88	0.192	33.1	70000
DV07020_12L	-FG/RD	B	12	5.0 to 13.2	0.30	3.60	4400	0.823	29.06	7.01	0.276	39.4	70000
DV07020_12M	-FG/RD	B	12	5.0 to 13.2	0.40	4.80	5200	1.059	37.39	9.30	0.366	43.2	70000
DV07020_12H	-FG/RD	B	12	5.0 to 13.2	0.50	6.00	6000	1.213	42.85	12.15	0.478	47.7	70000
DV07020_12U	-FG/RD	B	12	5.0 to 13.2	0.70	8.40	6800	1.307	46.17	14.63	0.576	50.6	70000

