

BLOWER DC FANS

BA SERIES Ø51×25 mm

- * Material: Impeller & Frame: Plastic (UL 94V-0)
- * Lead Wires: UL 1061 AWG #26 or Equivalent
- * Impeller: 31 Blades
- * Rotational direction CCW view from front face
- * Weight: 26g (1.27 OZ)



ASIA VITAL COMPONENTS CO., LTD. Six Sigma

MODEL	Bearing Type	Rated Voltage	Operating Voltage Range	Rated Current	Rated Input Power	Speed	Maximum Air Flow	Maximum Air Pressure	Acoustic Noise	Life expectancy L _{10@40°C}			
PART NO.	SIGNAL	B.T.S.R	VDC	VDC	Amp	Watt	R.P.M.	m ³ /min	CFM	mmH ₂ O	IN H ₂ O	dB-A	hours
BA05125_12L	FG/RD	B	12	5.0 to 13.2	0.20	2.4	3500	0.1438	5.07	4.916	0.1935	29.42	70000
BA05125_12M	FG/RD	B	12	5.0 to 13.2	0.25	3.00	4500	0.1874	6.618	9.07	0.3571	38.34	70000
* BA05125_12H	FG/RD	B	12	5.0 to 13.2	0.30	3.60	5500	0.2256	7.965	15.02	0.5913	41.17	70000
BA05125_12U	FG/RD	B	12	5.0 to 13.2	0.35	4.20	6200	0.2621	9.255	20.382	0.8024	45.4	70000
BA05125_12S	FG/RD	B	12	5.0 to 13.2	0.45	5.40	7000	0.2981	10.527	27.801	1.0945	48.52	70000

