

BLOWER DC FANS

BA SERIES Ø100×33 mm

- * Material: Impeller & Frame: Plastic (UL 94V-0)
- * Lead Wires: UL 1007 AWG #24 or Equivalent
- * Impeller: 43 Blades
- * Rotational direction CCW view from front face
- * Weight: 180 g (6.35 OZ)



ASIA VITAL COMPONENTS CO., LTD. Six Sigma

MODEL	PART NO.	SIGNAL	Bearing Type B.T.S.R	Rated Voltage VDC	Operating Voltage Range VDC	Rated Current Amp	Rated Input Power Watt	Speed R.P.M.	Maximum Air Flow		Maximum Air Pressure		Acoustic Noise dB-A	Life expectancy L ₁₀ @40°C hours
									m ³ /min	CFM	mmH ₂ O	IN H ₂ O		
	BA10033_12L	-FG/RD	B	12	7.0 to 13.8	0.38	4.56	2700	0.685	24.20	18.93	0.745	48.0	120000
	BA10033_12M	-FG/RD	B	12	7.0 to 13.8	0.66	7.92	3200	0.812	28.67	29.18	1.149	52.4	120000
	BA10033_12H	-FG/RD	B	12	7.0 to 13.8	0.88	10.56	3600	0.910	32.13	34.45	1.356	54.7	120000
	BA10033_12U	-FG/RD	B	12	7.0 to 13.8	1.55	18.60	4200	1.094	38.63	50.59	1.992	58.5	105000
	BA10033_12S	-FG/RD	B	12	7.0 to 13.2	1.90	22.80	5000	1.290	45.57	73.64	2.900	62.5	105000
	BA10033_24L	-FG/RD	B	24	14.0 to 26.4	0.22	5.28	2700	0.685	24.20	18.93	0.745	48.0	120000
	BA10033_24M	-FG/RD	B	24	14.0 to 26.4	0.34	8.16	3200	0.812	28.67	29.18	1.149	52.4	120000
	BA10033_24H	-FG/RD	B	24	14.0 to 26.4	0.45	10.80	3600	0.910	32.13	34.45	1.356	54.7	120000

