

BLOWER DC FANS

BN SERIES Ø133×91 mm

- * Material: Impeller: Plastic(UL 94V-0) & Frame: Diecast Aluminum
- * Lead Wires: UL 1007 AWG #22 or Equivalent
- * Impeller: 5 Blades
- * Rotational direction CW view from front face
- * Weight: 700 g (24.69 OZ)



ASIA VITAL COMPONENTS CO., LTD. Six Sigma

MODEL		Bearing Type	Rated Voltage	Operating Voltage Range	Rated Current	Rated Input Power	Speed	Maximum Air Flow		Maximum Air Pressure		Acoustic Noise	Life expectancy L ₁₀ @40°C
PART NO.	SIGNAL	B.T.S.R	VDC	VDC	Amp	Watt	R.P.M.	m ³ /min	CFM	mmH ₂ O	IN H ₂ O	dB-A	hours
BN13391_12U	-FG/RD	B	12	8 to 14	2.70	32.4	3900	5.94	209.63	39.2	1.54	62.0	100000
BN13391_24U	-FG/RD	B	24	16 to 28	1.30	31.2	3900	5.94	209.63	39.2	1.54	62.0	100000
BN13391_24S	-FG/RD	B	24	16 to 28	2.00	48.0	4500	7.14	252.1	56.1	2.21	67.0	100000
BN13391_24F	-FG/RD	B	24	16 to 28	2.60	62.4	4700	7.46	263.3	61.2	2.21	68.0	100000
BN13391_48U	-FG/RD	B	48	32 to 57	0.70	33.6	3900	5.94	209.63	39.2	1.54	62.0	100000
BN13391_48S	-FG/RD	B	48	32 to 57	1.00	48.0	4500	7.14	252.1	56.1	2.21	67.0	100000

