

BLOWER DC FANS

BN SERIES Ø175×69 mm

- * Material: Impeller (UL 94V-0) & Frame: Diecast Aluminum
- * Lead Wires: UL 1007 AWG #22 or Equivalent
- * Impeller: 7 Blades
- * Rotational direction CW view from front face
- * Weight: 830g (29.28 OZ)



MODEL		Bearing Type	Rated Voltage	Operating Voltage Range	Rated Current	Rated Input Power	Speed	Maximum Air Flow		Maximum Air Pressure		Acoustic Noise	Life expectancy L ₁₀ @40°C
PART NO.	SIGNAL	B.T.S.R	VDC	VDC	Amp	Watt	R.P.M.	m ³ /min	CFM	mmH ₂ O	IN H ₂ O	dB-A	hours
BN17569_24L	-FG/RD	B	24	14 to 27.6	1.00	24.0	2700	7.892	278.72	29.8	1.173	62.5	70000
BN17569_24M	-FG/RD	B	24	14 to 27.6	1.50	36.0	3100	9.086	320.86	40.0	1.575	66.0	70000
BN17569_24H	-FG/RD	B	24	14 to 27.6	2.30	55.2	3600	10.575	373.44	54.1	2.130	69.5	70000
BN17569_48L	-FG/RD	B	48	32 to 80	0.50	24.0	2700	7.892	278.72	29.8	1.173	62.5	70000
BN17569_48M	-FG/RD	B	48	32 to 80	0.75	36.0	3100	9.086	320.86	40.0	1.575	66.0	70000
BN17569_48H	-FG/RD	B	48	28 to 60	1.15	55.2	3600	10.575	373.44	54.1	2.130	69.5	70000
BN17569_48U	-FG/RD	B	48	28 to 53	1.55	74.4	4000	11.68	412.46	67.4	2.654	72.5	70000

